

MC2 UGELLO GETTO PIATTO FLAT SPRAY NOZZLES BOQUILLAS DE SALIDA PLANA

Caratteristiche

Ugello per basse portate a corpo unico, attacco maschio con o senza filtro.

Characteristics

Low capacities nozzle one piece made, male connection with filter or not.

Características

Boquilla para bajo caudal de una sola pieza. Rosca de conexión macho con o sin filtro.

Angoli di spruzzo disponibili:
0°- 15°- 25°- 40°- 50°- 65°-
80°- 95°- 110°.

Available spray angles:
0°- 15°- 25°- 40°- 50°- 65°-
80°- 95°- 110°.

Ángulos de aspersión posibles:
0°- 15°- 25°- 40°- 50°- 65°-
80°- 95°- 110°.

Applicazioni

- Lavaggi.
- Raffreddamenti.
- Lubrificazioni.
- Trattamenti Superficiali.

Applications

- Washing.
- Cooling.
- Lubrifications.
- Surface treatments.

Aplicaciones

- Lavado.
- Enfriamiento.
- Lubricación.
- Tratamiento de superficies.

Materiali

Ottone, Aisi303, Aisi316L, altri su richiesta.

Materials

Brass, SS303, SS316L, other on request.

Materiales


Latón, Aisi303, Aisi316L, otros bajo pedido.

Dimensions (mm)


Connection	L	E	H
1/8"	22,0	13,0	42,5
1/4"	23,5	14,0	41,0




MC2



PLASTIC FILTER 100 MESH (1/8" SIZE)



SS FILTER 50 OR 100 MESH (1/4" SIZE)



Flow Factor	Dia. (mm)	US (gpm at 40 psi)	Pressure (Bar)									
			1	2	3	4	5	6	8	10	20	40
			Capacity (Lpm)									
0017*	0,28	0,017	-	0,05	0,067	0,08	0,09	0,09	0,11	0,12	0,17	0,24
0025*	0,33	0,028	-	0,09	0,11	0,13	0,14	0,16	0,18	0,20	0,28	0,40
0033*	0,38	0,033	0,08	0,11	0,13	0,15	0,17	0,18	0,21	0,24	0,34	0,47
0050*	0,46	0,051	0,12	0,16	0,20	0,23	0,26	0,28	0,33	0,37	0,52	0,73
0067*	0,53	0,066	0,15	0,21	0,26	0,30	0,34	0,37	0,42	0,47	0,67	0,95
01	0,66	0,099	0,23	0,32	0,39	0,45	0,50	0,55	0,64	0,71	1,01	1,42
015	0,79	0,149	0,34	0,48	0,59	0,68	0,76	0,83	0,96	1,08	1,52	2,15
02	0,91	0,198	0,45	0,64	0,78	0,90	1,01	1,10	1,27	1,42	2,01	2,85
03	1,10	0,30	0,69	0,98	1,20	1,39	1,55	1,70	1,96	2,19	3,10	4,38
04	1,30	0,41	0,92	1,31	1,60	1,85	2,07	2,26	2,61	2,92	4,13	5,84
05	1,40	0,51	1,15	1,63	2,00	2,31	2,58	2,83	3,27	3,65	5,16	7,30
06	1,60	0,58	1,33	1,88	2,30	2,66	2,97	3,25	3,76	4,20	5,94	8,40
07	1,70	0,74	1,62	2,29	2,80	3,23	3,61	3,96	4,57	5,11	7,23	10,22
08	1,80	0,81	1,85	2,61	3,20	3,70	4,13	4,53	5,23	5,84	8,26	11,68
10	2,00	0,99	2,3	3,2	3,9	4,5	5,0	5,5	6,4	7,1	10,1	14,2
15	2,40	1,49	3,4	4,8	5,9	6,8	7,6	8,3	9,6	10,8	15,2	21,5

* depending from flow factor, materials and spraying angle can change, contact our office for more details.